



Acme Packet Certification Certification Exams Boot camp & Braindump

[Acme Packet AP0-001](#)

Total Questions: 10
Version Demo

<https://dumpsarena.com>
sales@dumpsarena.com

QUESTION NO: 1

_____ is the percentage of a Net-Net 4000 peer advertisement time for the other peer in the high availability (HA) cluster to wait before considering the peer out of service.

- A. 200%
- B. percent-drift
- C. 310%
- D. standard-deviation-score

Answer: B

QUESTION NO: 2

Which three of the following are NAPT mappings that are pulled by the Standby node during media state checkpointing in high availability (HA) architectures?

- A. Source port
- B. Protocol ID
- C. Route
- D. Ingress Interface

Answer: A, B, C

QUESTION NO: 3

_____ are stored in NVRAM.

- A. Logs
- B. CDRs
- C. Boot parameters
- D. Backup configurations

Answer: C

QUESTION NO: 4

Examine the output below from the network interface configuration. When the Net-Net 4000 does not get an ARP response from the device configured as its gateway in the configured retry time period, it will _____.

- A. send traffic to the device configured in the sec-gateway field
- B. decrement its health score to 50 which may result in a failover to the standby
- C. use the Virtual Router Redundancy Protocol (VRRP) to determine a new default gateway
- D. use the Virtual Router Redundancy Protocol (VRRP) to the host(s) instead of the primary gateway

Answer: B

QUESTION NO: 5

The _____ field allows you to set the health score at which a Net-Net 4000, if it the standby peer in a high availability (HA) scenario, will switchover to the active state without waiting for any configured timers to expire.

- A. emergency-threshold
- B. health-threshold
- C. active-threshold
- D. switchover-threshold

Answer: A

QUESTION NO: 6

To view an existing multiple instance element configuration you can go to the correct branch of the configuration tree and _____.

- A. select the element and then issue the show command
- B. enter the name of the element and then issue the show command
- C. type show and select from the displayed list
- D. type show <element name>

Answer: A

QUESTION NO: 7

The h245-stage parameter in the H323 stack determines _____.

- A. The stage at which the Net-Net 4000 will start tunneling H.245 messages
- B. The point in the call where H.245 messages are allowed, given that the call has been connected
- C. The stage at which the Net-Net 4000 will indicate that a separate H.245 connection must be opened or will react to an external indication to open a separate H.245 connection
- D. The point at which H.245 will appear on stage

Answer: C

QUESTION NO: 8

A _____ is a logical definition on the Net-Net Session Director of a network or group of networks composed partly of devices that provide real-time communication sessions made up of signaling messages and potentially media flows.

- A. realm
- B. steering pool
- C. session agent group
- D. session agent

Answer: A

QUESTION NO: 9

Which one of the following statements about the SIP-NAT is TRUE?

- A. The Net-Net 4000 uses the SIP-NAT element to rewrite the contact-URI, the Via header and the SDP.
- B. The Net-Net 4000 uses the SIP-NAT to provide translation between a home address space and an external address space.
- C. The Net-Net 4000 uses the SIP-NAT to act as a service pipe to SIPD.
- D. You must have at least one SIP-NAT to route traffic between realms.

Answer: B

QUESTION NO: 10

The _____ feature instructs the Net-Net 4000 whether to locally store all bindings for endpoints not located behind a NAT.

- A. Registration caching
- B. Reverse latching
- C. Adaptive NAT traversal
- D. Hairpinning

Answer: A

DUMPSARENA