DUMPSARENA

Alcatel-Lucent Advanced Troubleshooting

Alcatel-Lucent 4A0-110

Version Demo

Total Demo Questions: 5

Total Premium Questions: 41

Buy Premium PDF

https://dumpsarena.com

sales@dumpsarena.com

QUESTION NO: 1

Two direct connected routers are running RIPv2, neighbors are up but there is no route in the RIP database. Review the configuration information below. What is the potential problem?

Node 1

```
router rip
group "test"
    neighbor "toPod2"
    exit
exit
```

Node 2

```
router rip
group "test"
    neighbor "toPod1"
    exit
exit
```

A. System interface is not added to the RIP protocol

B. No import policy is configured

C. No export policy is configured

D. Split-horizon has to be disabled in RIP

E. Message-size has to be configured with a non-zero value

ANSWER: C

QUESTION NO: 2

A LSP is configured with one primary path and one secondary path as below. What configuration is required to make the LSP non-revertive. Choose the best answer.

```
config>router>mpls>
            path "toRouter3-loose"
                no shutdown
            path "toRouter3-backup"
                hop 1 10.10.1.2  loose
                no shutdown
            lsp toRouter3
                to 10.10.1.3
                cspf
                primary "toRouter3-loose"
                    bandwidth 600
                secondary "toRouter3-backup"
                    standby
                    bandwidth 600
                    no shutdown
```

A. Turn off CSPF and remove all the bandwidth reservations

B. Remove the primary path and configure both paths as secondary

C. Under asp toRouter3? configure on-revertive


D. It is not possible to configure the LSP as non-revertive

E. MPLS fast re-route has to be enabled to make it non-revertive

ANSWER: B

QUESTION NO: 3

Refer to the diagram below, what encapsulation type and VLAN tag are required at point X for the PC to ping the IES interface?



A. qinq sap 1/1/1:6.0

B. qinq sap 1/1/1:6.*

C. dot1q sap 1/1/1:6

D. null sap 1/1/1

E. There is no way to make ping works in this case

ANSWER: D

QUESTION NO: 4

Which files have to exist on Compact Flash 3 during system initialization on the Alcatel 7x50?

A. iom.tim

B. boot.ldr

C. cpm.tim

D. config.cfg

E. bof.cfg

ANSWER: B E

QUESTION NO: 5

Which of the following debug statements can be used to troubleshoot if the OSPF adjacency is staying at xstart state? Select two answers.

A. Debug router ospf rtm

B. Debug router ospf packet dbdescr

C. Debug router ospf neighbor

D. Debug router ospf packet hello

E. Debug router ospf spf

ANSWER: B C

DUMPSARENA