

# DUMPS ARENA

## Docker Certified Associate (DCA) Exam

Docker DCA

Version Demo

Total Demo Questions: 10

Total Premium Questions: 171

Buy Premium PDF

<https://dumpsarena.com>

[sales@dumpsarena.com](mailto:sales@dumpsarena.com)

dumpsarena.com

**QUESTION NO: 1**

You have deployed a service to swarm. Which command uses the Docker CLI to set the number of tasks of the services to 5? (choose 2)

- A. 'docker service update --replicas=5 '
- B. 'docker replica update =5'
- C. 'docker update service =5'
- D. 'docker service replicas =5'
- E. 'docker service scale = 5''

**ANSWER: A E****QUESTION NO: 2**

You created a new service named 'http' and discover it is not registering as healthy. Will this command enable you to view the list of historical tasks for this service?

Solution: 'docker service inspect http'

- A. Yes
- B. No

**ANSWER: A****QUESTION NO: 3**

The Kubernetes yaml shown below describes a networkPolicy.

Will the networkPolicy BLOCK this traffic?

Solution: a request issued from a pod bearing the tier: backend label, to a pod bearing the tier: frontend label

- A. Yes
- B. No

**ANSWER: B**

**QUESTION NO: 4**

Which of the following modes can be used for service discovery of a Docker swarm service (Pick 2 correct answers)

- A. Virtual IP (VIP) with `--endpoint-mode vip`
- B. Overlay with `--endpoint-mode overlay`
- C. DNS Round-Robin with `--endpoint-mode dnsrr`
- D. Ingress with `--endpoint-mode ingress`
- E. Network Address Translation(NAT) with `--endpoint-mode nat`

**ANSWER: A C**

**QUESTION NO: 5**

Which of the following are types of namespaces used by Docker to provide isolation? (Choose 2.)

- A. Host
- B. Network
- C. Process ID
- D. Authentication
- E. Storage

**ANSWER: B C**

**QUESTION NO: 6**

Which of the following commands starts a Redis container and configures it to always restart unless it is explicitly stopped or Docker is restarted?

- A. `'docker run -d --restart-policy unless-stopped redis'`
- B. `'docker run -d --restart omit-stopped redis'`
- C. `'docker run -d --restart unless-stopped redis'`
- D. `'docker run -d --failure omit-stopped redis'`

**ANSWER: C**

**QUESTION NO: 7**

Your organization has a centralized logging solution, such as Splunk.

Will this configure a Docker container to export container logs to the logging solution? Solution: docker logs

A. Yes

B. No

**ANSWER: B**

#### QUESTION NO: 8

During development of an application meant to be orchestrated by Kubernetes, you want to mount the /data directory on your laptop into a container.

Will this strategy successfully accomplish this?

Solution: Add a volume to the pod that sets hostPath.path: /data, and then mount this volume into the pod's containers as desired.

A. Yes

B. No

**ANSWER: B**

#### QUESTION NO: 9

You are pulling images from a Docker Trusted Registry installation configured to use self-signed certificates, and this error appears:

'x509: certificate signed by unknown authority'.

You already downloaded the Docker Trusted Registry certificate authority certificate from <https://dtr.example.com/ca>.

How do you trust it? (Select two.)

A. Place the certificate in '/etc/docker/dtr/dtr.example.com.crt' and restart the Docker daemon on all cluster nodes.

B. Place the certificate in your OS certificate path, trust the certificate system-wide, and restart the Docker daemon across all cluster nodes.

C. Pass '-trust-certificate ca.crt' to the Docker client.

D. Pass '--insecure-registry' to the Docker client.

E. Place the certificate in '/etc/docker/certs.d/dtr.example.com/ca.crt' on all cluster nodes.

**ANSWER: D E**

**QUESTION NO: 10**

What is the difference between the ADD and COPY dockerfile instructions? (choose 2)

- A.** ADD supports compression format handling while COPY does not.
- B.** COPY supports regular expression handling while ADD does not.
- C.** COPY supports compression format handling while ADD does not.
- D.** ADD support remote URL handling while COPY does not.
- E.** ADD supports regular expression handling while COPY does not.

**ANSWER: D E**