DUMPS🏅ARENA

Administration of Veritas InfoScale Storage 7.3 for UNIX/Linux

Veritas VCS-261

Version Demo

Total Demo Questions: 10

Total Premium Questions: 81

Buy Premium PDF

https://dumpsarena.com

sales@dumpsarena.com

dumpsarena.com

QUESTION NO: 1

Which two caching modes are supported by SmartIO when a Veritas file system is mounted on a Veritas volume in a non-virtual environment? (Choose two.)

A. write caching

B. write-back caching

C. read caching

D. read-back caching

E. block-level read caching

ANSWER: B C

QUESTION NO: 2

Which two commands are used for thin reclamation? (Choose two.)

A. fsadm

B. vxdctl

C. vxdisk

D. vxtune

E. vxdmpadm

ANSWER: A C

QUESTION NO: 3

Veritas File System is an extent based file system.

Which two pieces of information form the basis of an extent? (Choose two.)

A. inode number

B. offset

C. length

D. format

E. block size

ANSWER: A B

QUESTION NO: 4

Which attribute is used to create more than two mirrors of a volume?

A. nmirror

B. ncol

C. mirror

D. snapshot

ANSWER: C

QUESTION NO: 5

Which command is used to display current file system I/O parameters for a Veritas file system?

A. vxtune

B. vxtunefs

C. vxstat

D. fsadm

ANSWER: B

QUESTION NO: 6

Given the following command:

vxassist -g datadg make datavol 10g layout=stripe !ctrl:c2

Which instruction does the !ctrl:c2 attribute prompt Volume Manager to follow?

A. to exclude devices connected to controller c2

B. to exclude devices connected to all controllers except c2

C. to exclude devices from enclosure named "ctrl"

D. to exclude all but the fastest devices from controller c2

ANSWER: D

QUESTION NO: 7

Refer to the exhibit.

What is the layout of the volume described in the vxprint output provided in the exhibit?

A. mirrored volume with each mirror made up of concatenated subdisks (mirror-concat)

B. mirrored volume with each mirror made up of striped subdisks (mirror-stripe)

C. layered volume striped across mirrored subvolumes (stripe-mirror)

D. layered volume formed by concatenation of mirrored subvolumes (concat-mirror)

ANSWER: B

QUESTION NO: 8

Which two commands can an administrator use to remove the datadg02 disk from the datadg disk group based on the following configuration? (Choose two.)

```
                           ult       default    80000      1036905353.5.trcassun40
      datadg01          Disk_0    auto       20351      143328960  -
dm    datadg02          Disk_8    auto       20351      143328960  -

v     data              -                   ENABLED    ACTIVE     6146304    ROUND    -       gen
pl    data-01           data                ENABLED    ACTIVE     6146304    CONCAT   -       RW
sd    datadg01-05       data-01    datadg01  22539839   6146304    0         Disk_0   ENA
pl    data-02           data                ENABLED    ACTIVE     6146304    CONCAT   -       RW
sd    datadg02-03       data-02    datadg02  22539840   6146304    0         Disk_8   ENA
```

A. vxdg

B. vxdiskunsetup

C. vxplex

D. vxdisk

E. vxvol

ANSWER: A B

QUESTION NO: 9

A volume that contains strictly two data plexes and has four subdisks in each plex can have which two types of layouts? (Choose two.)

A. concat-mirror

B. stripe-mirror

C. stripe with parity

D. mirror-concat

E. mirror-stripe

ANSWER: D E

QUESTION NO: 10

Which Veritas InfoScale Storage feature is used when migrating Veritas File System data from thick to thin LUNs?

A. SmartIO

B. SmartMove

C. Compression

D. SmartTier

ANSWER: B