

DUMPS ARENA

Scalable WLAN Design and Implementation (SWDI) 8.4

HP HPE6-A71

Version Demo

Total Demo Questions: 10

Total Premium Questions: 166

Buy Premium PDF

<https://dumpsarena.com>

sales@dumpsarena.com

dumpsarena.com

QUESTION NO: 1

Which protocol is used to tunnel user traffic when an administrator implements tunneled mode between an ArubaOS-Switch and an Aruba Mobility Controller (MC)?

- A. IPSec
- B. AMON
- C. PAPI
- D. GRE

ANSWER: D

QUESTION NO: 2

When an administrator manually adds a Mobility Controller (MC) on the Mobility Master (MM) hierarchy, which parameters must be specified? (Select three.)

- A. IP address
- B. Device type
- C. MAC address
- D. Hostname
- E. Serial number

ANSWER: B C D

QUESTION NO: 3

An administrator deploys an AP at a branch office. The branch office has a private WAN circuit that provides connectivity to a corporate office controller. An Ethernet port on the AP is connected to a network storage device that contains sensitive information. The administrator is concerned about sending this traffic in

clear-text across the private WAN circuit.

What can the administrator do to prevent this problem?

- A. Redirect the wired port traffic to an AP-to-controller GRE tunnel.
- B. Convert the campus AP into a RAP.

- C. Enable AP encryption for wired ports.
- D. Enable IPSec encryption on the AP's wired ports.

ANSWER: B

QUESTION NO: 4

An administrator creates new pre-and post-authentication roles for a new WLAN. For which profile should the administrator assign these new roles under the Managed Network section?

- A. Server Groups
- B. Virtual AP
- C. 802.1X
- D. AAA profile

ANSWER: D

QUESTION NO: 5

Which methods can be used to configure RAP redundancy when connected to two redundant Aruba Mobility Controllers (MCs) in the DMZ? (Select two.)

- A. Virtual IP address of the two controllers.
- B. Active and Standby AAC.
- C. Primary and backup LMS IP addresses.
- D. IPSec High Availability (HA) between two cluster members.
- E. AirWave direction to RAPs redundant Mobility Controllers.

ANSWER: B C E

QUESTION NO: 6

In a cluster-controller environment, which Aruba component in a network builds a cache table of mDNS records that can be used to help user devices access Apple Bonjour services?

- A. the Mobility Master
- B. any Aruba Mobility Controller
- C. the Mobility Controllers that are cluster members
- D. the Mobility Master and cluster members

ANSWER: A

Explanation:

The MM maintains a cache table of mDNS records for all mDNS service advertisements that it sees

QUESTION NO: 7

An administrator inherits an Aruba Mobility Controller (MC) that has an unknown username and password.

Which credentials should the administrator enter to reset the administrative access?

- A. Username: backdoor; Password: @ruba
- B. Username: admin; Password: admin
- C. Username: password; Password: forgetme!
- D. Username: Aruba; Password: Reset!

ANSWER: C

Explanation:

References:

QUESTION NO: 8

What are the responsibilities of a cluster leader in a cluster of Aruba Mobility Controllers (MCs)? (Choose two.)

- A. To identify primary and secondary Mobility Controllers for APs
- B. To create a table to determine how a wireless client maps to a cluster member
- C. To identify a backup cluster leader for redundancy
- D. To manage the configuration of cluster members

E. To automatically load balance clients if the load across cluster members changes

ANSWER: B E

Explanation:

References:

QUESTION NO: 9

An administrator configures an ArubaOS-Switch for per-user tunneled node. Which protocols does the switch use to establish and maintain a connection with the Aruba Mobility Controller (MC)? (Select two.)

- A. GRE
- B. SSL
- C. PAPI
- D. IPSec

ANSWER: A C

QUESTION NO: 10

An Administrator supports a group of employees that connect to the corporate office using the VIA client. An Aruba Mobility Controller (MC), behind a corporate firewall, terminates the user's VPN sessions. The VPN sessions fail to establish because of the existing firewall rules.

Which connections must the administrator allow on the firewall? (Choose three.)

- A. UDP 8202
- B. UDP 4500
- C. UDP 8211
- D. TCP 4443
- E. TCP 443
- F. UDP 500

ANSWER: B E F